

Cleaning Adimar

The Adimar cleaner is an acid cleaner specially formulated with surfactant agents and corrosion inhibitors for the removal of cement waste, adapted to all intensive cleaning work.

Composition

Cleaning acid specially formulated with surfactants and corrosion inhibitors.

Application field

Cleaning of ceramic tiles and mosaics of all kinds, on floors, walls and facades, both inside and outside.

Elimination of efflorescences and salnitre from ceramic corners (cured earth, bricks) and unions.

Cleaning of dirt: cement waste, dust, lime, cement glue, etc. Remove collar remains: griffi, ADIMAR universal joint or ADIMAR 0/16 technical attachment, etc.

Cleaning of small yolk spots.

Cleaning pools.

Usage mode

The ADIMAR CLEANER can be used pure or diluted up to a ratio of 1:10 with tap water, depending on the type of application, resistance of dirt to be extracted, and resistance of the tiles (do previous tests in a corner).

ADIMAR CLEANER is easily applied to brush, sponge or spray. We help you with intense brushing.

In case of ecflorescence in the junctions between the tiles, apply ADIMAR CLEANER with a ratio of 1:10, brushing correctly and rinsing abundantly the water after 5 minutes.

Recommendations for use

Do not use ADIMAR CLEANER at:

On marble, calcareum or its derivatives.

Technical data

Product	Type		Cleaning acid with surfactants	
	Density	1,1 g/cm ³	pH	1
Consumption	Depending on the degree of dirt and the number of applications. Approximately 0.05 l/m ² .			
Storage	12 months	Store in a covered, dry and ventilated place with the container closed		
Presentation	Available from pure to diluted 1:10 with water, in 5 l. to 35 l. bottles.			

To know the security precautions related to the use, storage and elimination of the product, see the list of security data available on the website: www.aymarsa.es

NOTE: The information contained in this technical sheet is based on our experience and on trials carried out in specialized laboratories. The characteristics of the resulting product will depend on the correct preparation and application on site by the user. If these conditions are not met, the above characteristics will not be achieved.



Factory and Offices
 Ctra. C-35, Km 58 · Ap. correos nº1
 08470 SANT CELONI (Barcelona)
 Tel. (+34) 93 867 00 00
 aymar@aymarsa.es
www.aymarsa.es

