

DECLARATION OF PERFORMANCE

In accordance with the European Regulation of Construction Products nº 305/2011

Nº MR005.00-250710



EN 998-1:2016

1. PRODUCT

MORTARS FOR PLASTERING AND RENDERING

GREY M5
GREY M7,5
GREY M7,5H
SOLICEOUS GREY M5
SOLICEOUS GREY M7,5
SOLICEOUS GREY M7,5H
LIME GREY M5b
WHITE M5H
WHITE M7,5H
REVEMAR RENDER THICK LAYER WHITE/GREY
REVEMAR RENDER THICK LAYER WHITE/GREY
REVEMAR PROYECTABLE WHITE/GREY
REVEMAR PROYECTABLE HIIDROPHOUG GREY
RÚSTIC
REVEMAR PLASTER M16 HIGH RESISTANCES

2. MANUFACTURER'S NAME AND ADDRESS

AYMAR S.A.U.

Carretera C-35 KM.58,
08470 SANT CELONI (BARCELONA)

3. INTENDED USE

- Mortars for plasters and rendering, EN 998-1:2016.**
Commonly used in plastering and plastering for finishing walls, ceilings, pillars and partitions.

4. SYSTEM FOR EVALUATING AND VERIFYING THE CONSTANCY OF BENEFITS

System 4

• Page 1 de 2•



Plant and Offices

Ctra. C-35, Km 58 · Ap. Correos nº1
08470 SANT CELONI (Barcelona)

Tel. (+34) 93 867 00 00

aymar@aymarsa.es
www.aymarsa.es

5. DECLARED PERFORMANCES

ESSENTIAL FEATURES		TECHNICAL SPECIFICATIONS	U.	PRESTACIONES														
				GREY M5	GREY M7,5	GREY M7,5H	SOLICEOUS GREY M5	SILICEOUS GREY M7,5	SILICEOUS GREY M7,5H	LIME GREY M5	WHITE M5H	WHITE M7,5H	REVENMAR PROJECTABLE WHITE/GREY	REVENMAR PROJECTABLE WATER-REPELLENT GREY	REVENMAR RENDER THICK LAYER WHITE/GREY	REVENMAR RENDER THIN LAYER WHITE/GREY	RUSTIC	REVENMAR PLASTER M16 HIGH RESISTANCES
Kneading water	-	EN 998-1:2016	%	15-16%	15-16%	15-16%	15-16%	15-16%	15-16%	15-16%	15-16%	15-16%	15-16%	15-16%	15-16%	20-25%	18%	16%
Consistency	EN 1015-3		mm	185 ±10	185 ±10	185 ±10	175 ±10	175 ±10	175 ±10	185 ±10	185 ±10	185 ±10	160 ±10	160 ±10	160 ±10	170 ±10	180 ±10	160 ±10
Bulk density of dry hardened mortar	EN 1015-10		Kg/m³	1800-2000	1800-2000	1800-2000	1800-2000	1800-2000	1800-2000	1800-2000	1800-2000	1800-2000	1200-1700	1200-1700	1600-1800	1000-1500	1500-1900	1600-1800
Compressive strength	EN 1015-11		Category	CS III	CS IV	CS IV	CS III	CS IV	CS III	CS III	CS III	CS IV	CS III	CS III	CS IV	CS III	CS III	CS IV
Adhesion	EN 1015-11		Concrete support N/mm2	>0,2	>0,3	>0,3	>0,2	>0,3	>0,3	>0,2	>0,3	>0,5	>0,3	>0,3	>0,3	>0,4	>0,3	>0,4
Water absorption by capillarity	EN 1015-18		Category	Wc0	Wc0	Wc2	Wc0	Wc0	Wc2	Wc0	Wc2	Wc2	Wc0	Wc1	Wc2	Wc2	Wc2	Wc2
Water vapor permeability	EN 1015-19		Potassium Nitrate Reagent μ	<14	<15	<15	<10	<15	<15	<12	<8	<15	<10	<10	<10	<10	<15	<10
			Lithium Chloride Reagent μ	<14	<15	<15	<10	<15	<15	<12	<8	<15	<10	<10	<10	<10	<15	<10
Thermal Conductivity	EN 1745 (Table A.12) Tabulated value		λ _{10,dry} (W/mK)	0,96	0,96	0,96	0,96	0,96	0,96	0,96	0,96	0,96	0,45	0,45	0,71	0,37	0,66	0,71
Reaction to Fire	EN 998-1		Class	A1	A1	A1	A1	A1	A1	A1	A1	A1	A1	A1	A1	A1	A1	A1
Durability			NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD	

The performance of the product identified in point 1 is in accordance with the performance declared in point 5. This declaration of performance is issued under the sole responsibility of the manufacturer indicated in point 2.



Luís Jesús García-Muñoz Miras
 Responsible for the Integrated Management System
Quality, Occupational Safety, Environment, Sustainable Mining
 Sant Celoni, July 10, 2025

Plant and Offices

Ctra. C-35, Km 58 · Ap. Correos nº1
 08470 SANT CELONI (Barcelona)

Tel. (+34) 93 867 00 00

aymar@aymarsa.es

www.aymarsa.es