

SAFETY DATA SHEET

HIGH-STRENGTH PLASTER MORTARS

Compliant with Regulation (EC) No 1907/2006 (REACH)

Edition 1. Revision 00-10/07/2025

1. Product and company identification.

1.1. Product Identifier.

Product Name

HIGH-STRENGTH PLASTER MORTARS

1.2. Product Application.

Our mortars are duly certified for use in high-strength plaster and plaster work (according to UNE-EN 998-1), in the European Community.

1.3. Identification of the manufacturing company.

AYMAR S.A.U. Plant & Offices. Ctra. C-35, Km 58 · Ap. Correos nº1. 08470 SANT CELONI (Barcelona).

Tel. (+34) 93 867 00 00

aymar@aymarsa.es

www.aymarsa.es

1.4. Emergency telephone number.

National Institute of Toxicology: 915 62 04 20

2. Hazard identification.

2.1. Classification.

Skin Irritation, Category 2 (H315).

Serious eye injuries, Category 1 (Eye Dam. 1, H318).

Skin sensitization, Category 1 (Skin Sens. 1, H317).

Skin Irritation 2 (H335)

2.2. Label Elements.

Regulation (EC) No 1272/2008

Pictograms:	 GHS05 Corrosion	 GHS07 Attention
Phrases H:	H318: Causes serious eye injuries. H315: Causes skin irritation H335: May irritate the airways	

Phrases P:	<p>Precautionary Advice-Prevention:</p> <ul style="list-style-type: none"> • P264: Wash hands thoroughly after handling • P280: Wear protective gloves/clothing/goggles/mask. <p>Precautionary Advice-Answer:</p> <ul style="list-style-type: none"> • P302+P352+ P333+P313: IN CASE OF CONTACT WITH SKIN: Wash with plenty of soap and water. In case of irritation or rash: consult a doctor. • P321: Specific treatment is needed • P362 + P364: Remove contaminated clothing and wash it before using it again. • P305+P351+P338 + P310: IN CASE OF CONTACT WITH EYES: Rinse carefully with water for several minutes. Remove contact lenses, if you have one, and it's easy. Keep clarifying. If the eye irritation: Consult a doctor. <p>Precautionary Advice-Storage:</p> <ul style="list-style-type: none"> • P403+P233: Store in a well-ventilated place. Keep the container tightly closed. • P501: Dispose of the contents or container in accordance with local, regional, national, or international regulations
------------	--

2.3. Other hazards:

Not relevant

Environment

The mortar does not present a particular risk to the environment, provided that the considerations in paragraphs 12 and 13 of Ecological Information and Disposal Considerations are respected.

Additional information:

The marketed product is poor in chromates per se or due to the reduction of its content in water-soluble Chromium VI.

3. Composition/information about its components.

3.1. Composition.

Mixture of cements, aggregates and additives.

3.2. Hazardous components:

Component	N° CAS	N° EINECS	Concentration %	Danger symbol	H-Phrases
Cement	65997-15-1	266-043-4	< 25	GHS05, GHS07	H318, H315, H335
Calcium hydroxide	1305-62-0	215-137-3	< 5	GHS05, GHS07	H318, H315, H335

4. First aid.

4.1. Description of First Aid.

Inhalation

Moving the source of contamination or moving the victim to a place with fresh air. Get medical advice immediately.

Skin contact

If there is irritation, clean the affected area with a jet of warm water, let the water run gently for at least 10 minutes. If irritation persists, get medical advice immediately.

Eye contact

Immediately clean the contaminated eye(s) with a stream of warm water, let the water run gently for 10 minutes keeping the eyelid(s) open. If irritation persists, get medical advice immediately.

Ingestion

Never give anything through the mouth, if the victim is losing consciousness, or is unconscious or convulsed. Rinse your mouth thoroughly. DO NOT INDUCE VOMITING. Give the victim 240 to 300 ml of water to drink to dilute the material in the stomach. Get medical advice immediately.

Provide general support measures (warmth, comfort and rest). If the situation worsens, transfer the patient to the nearest poison control center.

4.2. Main symptoms and effects, acute and delayed.

No symptoms or delayed effects

4.3 Indication of any medical care and special treatments to be given immediately.

Not relevant.

5. Firefighting measures.

5.1. Means of extinguishing.

Non-flammable product under normal conditions of storage, handling and use. In the event of ignition as a result of improper handling, storage or use, preferably use multipurpose powder extinguishers (ABC powder), in accordance with the Regulation on Fire Protection Installations (R.D. 1942/1993 and subsequent amendments).

It is **NOT RECOMMENDED** to use jet water as an extinguishing agent.

5.2. Specific hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition, reactions by-products (CO₂, CO, NO_x,...) are generated that can be highly toxic and, consequently, can pose a high risk to health.

5.3. Recommendations for firefighting personnel.

Depending on the magnitude of the fire, it may be necessary to wear full protective clothing and self-contained breathing equipment. Have a minimum of emergency installations or action elements (fireproof blankets, portable first aid kit,...) in accordance with R.D.486/1997 and subsequent amendments

5.4. Additional provisions.

Act in accordance with the Internal Emergency Plan and the Information Sheets on action in the event of accidents and other emergencies. Suppress any source of ignition. In the event of fire, refrigerate containers and storage tanks for products susceptible to ignition, explosion or BLEVE because of high temperatures. Avoid the spillage of the products used in extinguishing the fire into the aquatic environment.

6. Measures to be taken in the event of accidental spillage.

6.1. Individual precautions.

Avoid breathing dust. Use respiratory protection in poorly ventilated places.

Avoid contact with eyes and skin. Wear eye protection goggles, appropriate work clothes and waterproof safety gloves.

6.2. Precautions for environmental protection.

Avoid contamination of drains, surface water, and groundwater.

6.3. Cleaning Methods.

Collect by mechanical means avoiding the formation of dust. Clean the stained area with plenty of water.

Dispose of recovered waste in accordance with current local regulations.

After setting up, the product can be evacuated as inert waste.

6.4. Reference to other sections.

See sections 8 and 13.

7. Handling and storage.

7.1. Precautions for safe handling.

The supply of this material is carried out in paper, plastic or bulk bags.

In the premises where the product is handled, good ventilation must be guaranteed.

Avoid dust clouds during handling. If it is unavoidable, wear approved goggles and dust mask.

Avoid contact with skin and eyes.

7.2. Safe storage conditions, including possible incompatibilities.

Keep the container tightly closed and protected from exposure to air and moisture. Store in a dry and cool place away from the normal work area and incompatible materials.

Burial hazard: to prevent the risk of burial or suffocation, do not enter confined spaces such as silos, containers, vats or other containers that are used for storage or contain mortar without taking appropriate safety measures. The mortar can accumulate or stick to the walls of confined spaces and can come loose.

7.3. Specific End Uses.

In mortars treated with Chromium VI reducing agent, the effectiveness of the reducing agent decreases over time. Therefore, bags and packing slips must include information on the period of efficacy (expiry date, half-life) that the manufacturer guarantees that the reducing agent will continue to maintain the level of Chromium VI below the regulatory limit of water-soluble Chromium VI. In addition, appropriate storage conditions should be indicated to maintain the effectiveness of the reducing agent.

8. Exposure/personal protection controls.

8.1. Control parameters.

Substances included in the "Occupational Exposure List for Chemical Agents in Spain" of the NIOSH (National Institute for Occupational Safety and Health):

Component	Nº CAS	Nº EINECS	Type	Limit value
Portland Cement	65997-15-1	266-043-4	VLA-ED Respirable fraction (8 hours)	4 mg/m ³
Calcium hydroxide	1305-62-0	215-137-3	VLA-ED (8 hours) VLA-EC (15 minutes)	1 mg/m ³ 4 mg/m ³

8.2. Exposure controls.

General:

During work, whenever possible, avoid kneeling in concrete or fresh mortar. If it is absolutely necessary to kneel to carry out the work, then the use of waterproof personal protective equipment (waterproof knee pads) is mandatory. Do not eat, drink or smoke while carrying out mortar work to prevent it from coming into contact with the skin or mouth.

Once the mortar work is finished, workers must wash, shower and it is advisable to use moisturizers. Remove any stained clothing (clothing, footwear, watches, etc.) and clean it before using it again.

Respiratory protection:

Use an approved breathing guard to avoid the discomfort of dust. Limitations on the use of the breathing shield are specified by the certifying agency and the manufacturer.

Eye protection:

To avoid the risk of dust and projections on the eyes, it is necessary to wear safety glasses.

Skin protection:

Waterproof gloves, body protectors, etc. will necessarily have to be worn. Wash hands during shutdowns and at the end of work

Environmental exposure control:

According to the available technology.

9. Physical and chemical properties.

9.1. Information on basic physical and chemical properties.

Aspect:	Granulate and powder
Smell:	Odorless
PH in aqueous solution:	11-13
Bulk density:	1,4-2 g/cm ³ .
Solubility in water:	The product is partially soluble.
Boiling Point:	not applicable.
Flash Point:	not applicable.
Melting Point:	> 1000°C.
Autoignition time.:	Not applicable
Decomposition time:	Not applicable

10. Stability and reactivity.

10.1. Reactivity.

Hazardous reactions are not expected if the technical instructions for chemical storage are followed. See section 7.

10.2. Chemical stability.

Stable in dry storage conditions and once set.

10.3. Possibility of dangerous reactions.

Under the above conditions, no dangerous reactions are expected that may produce excessive pressure or temperatures.

10.4. Conditions to be avoided.

Exposure to moisture prior to application may result in product hardening.

10.5. Subjects to avoid.

Strong acids

10.6. Hazardous Breakdown Products.

Not known

11. Toxicological information.

11.1. Information on toxicological effects.

No experimental data is available on the mixture itself relating to toxicological properties. When classifying the hazard of corrosive or irritating effects, the recommendations contained in section

3.2.5 of Annex VI of R.D.363/1995 (Directive 67/548/EC), in paragraphs b) and c) of paragraph 3 of article 6 of R.D.255/2003 (Directive 1999/45/EC) and in section 3.2.3.3.5. of Annex I of the CLP Regulation.

Dangerous health effects:

Inhalation:	It can irritate the respiratory system. The symptoms are sneezing and slight nasal irritation.
Skin contact:	May cause caustic irritations and burns.
Eye contact:	Mild irritation. Symptoms are watery eyes and irritation.
Ingestion:	If swallowed, it can cause irritation of the digestive tract and abdominal pain.

Acute effects:

Eye contact:	Direct contact with mortar can cause damage to the cornea due to mechanical stress, irritation and immediate or delayed inflammation. Contact with large amounts of mortar (powder or splashes of fresh pasta) can produce keratoplasties of different considerations.
Skin contact:	The mortar can irritate damp skin because the cement pastes have a high pH. Skin contact without adequate protection with mortar pastes can lead to dermis injuries such as cracking or caustic burns without any previous symptoms.
Acute dermal toxicity:	Test parameters, rabbit, 24 hours of contact, 2,000 mg/kg body weight - no mortality.
Ingestion:	In case of significant ingestion, the mortar can cause irritation and pain in the digestive tract.
Inhalation:	The mortar can cause irritation of the throat and respiratory tract. Exposures to concentrations above occupational exposure limit values can cause coughing, sneezing and shortness of breath.

Chronic effects:

Inhalation:	Chronic exposure to respirable dust concentrations above occupational exposure limit values can lead to coughing, shortness of breath and chronic obstructive pulmonary disease (COPD).
Carcinogenicity:	No causal relationship has been established between mortar exposure and the development of cancer.
Contact dermatitis / Sensitizing effects:	Some individuals exposed to fresh mortar paste may develop eczema, caused either by the high pH inducing contact dermatitis or by an immunological reaction to Chromium VI leading to allergic contact dermatitis (Reference (4)). The provoked reaction is a combination of these two mechanisms, and its effects can range from a mild rash to severe dermatitis. It is often difficult to make an accurate diagnosis. In mortars containing Chromium VI reducing agent, provided that their period of effectiveness guaranteed by the manufacturer (periods indicated on the bag or delivery note) is not exceeded, it is not likely that any sensitizing effect will develop.

Aggravation of previous illnesses due to exposure:

Breathing in mortar dust can aggravate the symptoms of previously diagnosed diseases such as respiratory pathologies, emphysema, asthma, eye pathologies and skin pathologies.

12. Ecological information.

There are no known negative effects on the environment once the product has set.
The hardened material is a stable material that fixes its compounds and makes them insoluble.
Dumping the product into the water can cause an increase in pH.

Non-biodegradable.

12.1. Toxicity.

Not determined

12.2. Persistence and degradability.

Not determined

12.3. Bioaccumulation Potential.

Not determined

12.4. Mobility on the ground.

Not described

12.5. PBT and mP assessment results.

Not applicable

12.6. Other side effects.

Not applicable

13. Considerations relating to elimination.

13.1 Methods for waste treatment.

Product:

Following the local regulations in force as construction waste.
Do not discharge it into sewers or waterways.

Containers and packaging:

Empty containers and packaging can be recycled.
Containers and packaging with product must be disposed of in the same way as the product.

14. Information relating to transport.

Non-dangerous goods.

Not subject to transport classification and labelling.

15. Regulatory Information.

15.1. Safety, health and environmental legislation and regulations specific to the substance or mixture.

Candidate substances for authorization in Regulation (EC) 1907/2006 (REACH): Not relevant

Regulation (EC) 1005/2009 on substances that deplete the ozone layer: Not relevant

Active substances which have not been included in Annex I or IA of Directive 98/8/EC: Not relevant

Regulation (EC) 689/2008 on the export and import of hazardous chemicals: Not relevant

Restrictions on the marketing and use of certain dangerous substances and mixtures (Annex XVII of the REACH Regulation):

Not relevant

Specific provisions on the protection of people or the environment:

It is recommended that the information collected in this safety data sheet be used as input data in a risk assessment of local circumstances in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

Not applicable

15.2. Chemical Safety Assessment.

The supplier has not carried out a chemical safety assessment.

16. Other information.

Modifications with respect to the previous safety data sheet that affect risk management measures:

The hazard statement "H317: May cause an allergic skin reaction" and relative cautionary phrases are removed, as cement is declassified as a skin sensitizer, according to the supplier's SDS.

The percentage concentration of hazardous cement and lime components considered in products under the scope of this SDS is reduced.

Advice regarding training: Minimum training in occupational risk prevention is recommended for personnel who are going to handle this product, to facilitate the understanding and interpretation of this safety data sheet, as well as the labelling of the product

Full H-phrases from section 3:

H318: Causes serious eye injuries.

H315: Causes skin irritation

H335: May irritate the airways

The information in this Product Safety Data Sheet is based on current knowledge and current EC and national laws, as the working conditions of users are beyond our knowledge and control. The product must not be used for purposes other than those specified, without first having a written instruction for its operation. It is always the responsibility of the user to take the appropriate measures to comply with the requirements established in the legislation.



Plant & Offices

Ctra. C-35, Km 58 · Ap. Correos nº1
08470 SANT CELONI (Barcelona)

Tel. (+34) 93 867 00 00

aymar@aymarsa.es
www.aymarsa.es

