



ADHESION PROMOTER

FIXMAR PRIMER GR



INTERIOR AND EXTERIOR



RED

Applications

FIXMAR PRIMER GR is ideal for improving the adhesion of any type of plaster or render to concrete, brick, lightweight concrete blocks, or plaster substrates, as well as to non-absorbent surfaces such as ceramic tiles. For walls and floors, both indoors and outdoors. It is also suitable for application on non-absorbent surfaces such as ceramic tile, in preparation for the subsequent installation of ceramic tile or natural stone.

On porous cement or anhydrite floors, or on sanded floors, **FIXMAR PRIMER GR** acts as a binder for dust residues, thereby facilitating proper adhesion of a self-leveling mortar. It also acts as a pore filler.

Instructions for Use

- **Substrate Preparation:** Surfaces must be clean, dry, cured, and free of oil, grease, and loose debris. It is not necessary to dampen the substrate before application.
- **Applying the Primer:** Shake well before use and apply to the surface using a brush or roller. Once the curing time has elapsed, you may proceed with the application of the coating, plaster, or self-leveling mortar.

Primer and adhesion promoter based on acrylic polymers with low emissions of volatile organic compounds. Ready-to-use for interior and exterior applications, with inert fillers that give it a textured surface.



12 months

5 Kg
approx.

Recommendations for Use

- Apply when the substrate temperature is between 5 °C and 35 °C.
- Protect from freezing.
- Do not use FIXMAR PRIMER GR if there is rising damp.
- Clean tools with water after applying the primer.
- A second coat of FIXMAR PRIMER GR may be applied even if a long period of time has elapsed since the first application.
- On porous or absorbent surfaces, the product may be diluted with water up to 20%.
- The waiting time before applying the skim coat, rough coat, or self-leveling mortar is 15 to 60 minutes, depending on the substrate and weather conditions.

Technical Specifications

| | | |
|---------------------|---|-----------------------------|
| Product | Appearance | Creamy liquid |
| | Color | Red |
| | Density | 1.4 ± 0.1 g/cm ³ |
| | pH | 8 |
| Application | Application temperature between 5 °C and 35 °C | |
| Coverage | 0.2–0.3 kg/m ² | |
| Storage | 12 months under normal conditions, in its original unopened packaging | |
| Product Description | FIXMAR PRIMER GR is available in 5 kg containers | |

For safety instructions regarding the use, storage, and disposal of the product, refer to the safety data sheet available on the website www.aymarsa.es

NOTE: The information contained in this technical data sheet is based on our experience and on tests conducted in specialized laboratories. The characteristics of the final product will depend on proper preparation and application on-site by the user. If these conditions are not met, the characteristics indicated above will not be achieved.



Plant and Offices
C-35 Highway, km 58
08470 SANT CELONI (Barcelona)
Tel. (+34) 93 867 00 00
aymar@aymarsa.es
www.aymarsa.es

